



## Brackets

|                    |   |
|--------------------|---|
| <b>Application</b> | For wall mounting of pressure and temperature gauges with capillary tube. |
| <b>Materials</b>   | Aluminium, black stove enamelling or silvery powder layer.                |
| <b>Execution</b>   | DIN 16281, form H   |
| <b>Use</b>         | Intermediate piece for N 5012 brackets. See D5.510.2                      |



### Selection Chart

| Dimensions | Projection L | Surface         | Ident. Number |
|------------|--------------|-----------------|---------------|
|            | 60           | Black lacquered | N 5011.0      |
|            |              | Silvery         | N 5011.1      |
|            | 100          | Black lacquered | N 5011.2      |
|            |              | Silvery         | N 5011.3      |
|            | 160          | Black lacquered | N 5011.4      |
|            |              | Silvery         | N 5011.5      |
|            |              |                 |               |
|            |              |                 |               |



## Bracket

|                   |  |
|-------------------|--|
| Application       | Fastens pressure gauges with extensive cables to walls, pipes or frames                |
| Material          | Galvanized cast iron, primed<br>Clamp screws, hexagon socket,<br>SWS, galvanized steel |
| Model             | DIN 16281 Type A   |
| Ident. Number     | J 64086.0100   |
| Product delivered | Bracket with clamp screws (screws for fastening to wall are not included)              |

