




Shut-Off Cocks

Application	For liquids, gases or vapours at operational pressures up to 25 bar and temperatures up to 50 °C
Materials	Brass Chrome-plated brass Nickel-plated brass Steel Stainless steel
Execution	Standardized according to DIN or SN and common commercial forms. With cock positions for relief and blow out. With or without test connection.



Selection Chart without test connection

Dimensions	Connections		Operational data		Material	Ident. Number
	Entry	Exit	Pressure bar	Temp. °C		
	Muff connection G ¹ / ₄	Muff connection G ¹ / ₄	6	50	Brass	D 7722.0
 DIN 16251 - AG	Muff connection G ¹ / ₂	Muff connection G ¹ / ₂	25	50	Brass	N 5003.0
					Chrome-plated brass	N 5003.1
	Tappet connection G ¹ / ₄	Muff connection G ¹ / ₄	6	50	Brass	D 11 723.0



Selection Chart without test connection

Dimensions	Connections		Operational data		Material	Ident. Number
	Entry	Exit	Pressure bar	Temp. °C		
<p>DN 16 261 - BG</p>	Tappet connection G ¹ / ₂	Muff connection G ¹ / ₂	25	50	Brass	N 5004.0
					Chrome-plated brass	N 5004.1
<p>DN 16 260 - BG</p>	Tappet connection G ¹ / ₄	Clamp muff connection G ¹ / ₄	6	50	Brass	N 5002.0
	Tappet connection G ³ / ₈	Clamp muff connection G ³ / ₈	10	50	Brass	D 7724.0
<p>DN 16 262 - AG</p>	Tappet connection G ¹ / ₂	Clamp muff connection G ¹ / ₂	25	50	Brass	N 5006.0
					Chrome-plated brass	N 5006.1
					Steel	N 5006.2
					Stainless steel	N 5006.3
	Muff connection G ¹ / ₂	Union nut connection G ¹ / ₂	25	50	Brass	D 11 724.0



Selection Chart with test connection

Dimensions	Connections		Operational data		Material	Ident. Number
	Entry	Exit	Pressure bar	Temp. °C		
<p>Test connection M20 x 1,5</p> <p>DIN 16 263 - AG</p>	Tappet connection G $\frac{1}{2}$	Clamp muff connection G $\frac{1}{2}$	25	50	Brass	N 5007.0
<p>Test flange 60 x 25 x 10</p>	Tappet connection G $\frac{1}{2}$	Clamp muff connection G $\frac{1}{2}$	25	50	Brass	D 11 728.0
<p>Test flange 60 x 25 x 10</p>	Tappet connection G $\frac{1}{2}$	Clamp muff connection G $\frac{1}{2}$	16	50	Brass	D 11 729.0
<p>Test connection G$\frac{1}{2}$</p>	Tappet connection G $\frac{1}{2}$	Clamp muff connection G $\frac{1}{2}$	25	50	Brass	D 7731.0



Selection Chart without test connection

Dimensions	Connections		Operational data		Material	Ident. Number
	Entry	Exit	Pressure bar	Temp. °C		
<p>With stop sleeve</p>	Muff connection G ¹ / ₂	Muff connection G ¹ / ₂	25	50	Brass	D 11 725.0
<p>With stop sleeve</p>	Tappet connection G ¹ / ₂	Muff connection G ¹ / ₂	25	50	Brass	D 11 726.0
<p>With push button operation</p>	Muff connection G ¹ / ₂	Muff connection G ¹ / ₂	25	50	Nickel-plated brass	D 11 727.0
suitable clamp strap						J 64 105.1